



- 01 **Easy:** Fast, simple installation for both wired and wireless models
- 02 **Versatile:** Compatible with most Hunter controllers
- 03 **Smart:** Shuts down irrigation the moment rain is detected

RAIN-CLIK® SENSORS

Rain-Click's Quick Response™ Stops Irrigation The Instant Rain Starts To Fall

Most rain-sensing devices work by accumulating a set amount of rainfall before a switch is activated that interrupts the circuit from the controller and shuts off the system. In that “accumulation time”, the system will unnecessarily continue to water. This can look especially bad for conservation-conscious municipalities, businesses, and residences. With built-in Quick Response technology, the Hunter Rain-Click and Wireless Rain-Click can command a controller to shut off right when it starts to rain. The Rain-Click can be mounted on an eave or any flat vertical surface like a wall or fence. A gutter mount is also available that allows for easy installation of the Rain-Click on the edge of a gutter.

RAIN-CLIK™ FEATURES & SPECIFICATIONS

Features

- Quick Response™ feature shuts the system off as soon as it starts raining
- Maintenance-free design with 10-year battery life for Wireless Rain-Clik™
- Adjustable vent ring allows for setting of reset delay
- Rugged polycarbonate housing and metal extension arm
- Rain-Clik includes 25 ft of 20 AWG sheathed, two-conductor, UL-approved wire
- Wireless unit available with 800 ft range from wireless sensor to receiver
- Compatible with most controllers
- Warranty period: 5 years (10 year battery warranty for wireless model)

Specifications

- Wiring: normally closed or normally open
- Time to turn off irrigation system: 2 to 5 minutes approx. for Quick Response
- Time to reset Quick Response: 4 hours approx. under dry, sunny conditions
- Time to reset when fully wet: 3 days approx. under dry, sunny conditions
- UL listed, CUL (CSA), CE
- Switch rating: 24 VAC, 3 A
- Freeze sensor shuts system off when temperatures fall below 37° F (Rain/Freeze-Clik model)
- System operating frequency: 433 MHz
- UL listed, FCC approved, suitable for use in Australia, CUL (CSA), CE
- Communication range up to 800 ft. line of sight (Wireless model)
- Rain/Freeze-Clik shuts system off when temperatures fall below 37° F
- Receiver input power: 24 VAC (from controller)

Models

RAIN-CLIK

Height: 2½"
Length: 7"



WIRELESS RAIN CLIK TRANSMITTER

(with metal arm)

Height: 3"
Length: 8"



WIRELESS RAIN CLIK RECEIVER

Width: 3¼"
Height: 4"



RAIN-CLIK™

Model	Description
RAIN-CLIK	Rain-Clik sensor
RFC	Rain/Freeze-Clik sensor
WR-CLIK	Wireless Rain-Clik system
WRF-CLIK	Wireless Rain/Freeze-Clik system

USER INSTALLED OPTION (Specify Separately)

Model	Description
SGM	Optional gutter mount (included in the WRF-CLIK)

Website hunterindustries.com | **Customer Support** 760-744-5240 | **Technical Service** 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Richard E. Hunter
Richard E. Hunter, CEO of Hunter Industries

